

SOLIS

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

20



SMART
ERGONOMICS DESIGN

EASY OPERATE
METAL BONNET

TWIN PROJECTOR
HEADLAMPS

AGRI/IND./TURF
TYRE OPTION

REINFORCED SAFETY
FEATURES



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

**STRATEGIC
COLLABORATION
WITH
YANMAR**



S20

Solis




FEATURES	S20
ENGINE	
Engine Type	3 Cylinder (Water Cooled) Engine
HP Category	20
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	953
Rated RPM	2700
Air Cleaner	Dry with Clogging Sensor
Cold Start	Standard
Max. Torque (Nm)	52
Exhaust	Silencer in The Engine Compartment, Downward Discharge
TRANSMISSION	
Drive	4WD
Clutch	Single Clutch
Gearbox	6 Forward + 2 Reverse
Front Axle	4WD
Transmission	Sliding Mesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	15.1@2900
Minimum Speed (Km/Hr)	1.36@rated
BRAKES	
Brakes	Dry Drum Brake
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential lock	Yes, Foot Operated
PTO	
PTO (RPM)	540, 1000
PTO (Actuation)	Mechanical
STEERING	
Steering	Power Steering
ELECTRICAL	
Battery	12 V, 60 Ah
Type of Actuation	12V, 42 A
Parking Brake	Standard
HYDRAULICS	
3 Point Linkage	Cat 1 - N
Stay Bars	Anchor Chain
Auxiliary Hydraulic Circuit	1DA
Lift Rods	Standard
Lifting Capacity (Kg)	600
Litre Per Minute (LPM)	13.3

FEATURES		S20	
SAFETY SWITCH 			
PTO Safety		Standard	
Neutral Safety Switch		Standard	
Clutch Safety Switch		Standard	
CAPACITY (LITRE) (+/-5%) 			
Fuel Tank (Ltr.)		26	
TURNING RADIUS 			
Without Brakes (m)		3.2 (RHS), 3.3 (LHS)	
TYRE (STANDARD) 			
Front		5.00-12	
Rear		8.00-18	
DIMENSION & WEIGHT (+/-5%) 			
Weight (kg)		970	
Wheel Base (mm)		1420	
Total Length (mm)		2735	
Total Width (mm)		945(max)-940(min)	
Height (mm) Up to ROPS		1945	
Min. Ground Clearance (mm)		200	
Front Track (mm)		805	
Rear Track (mm)		715	
OTHERS 			
Fuel Indicator Gauge		Standard	
Front Tow Hook		Standard	
Front & Rear Weights with Std. Ballast		Front weights 30 Kg - 2 x 15 Kg	
Trailer Hitch		Drawbar / Optional Towbar	
ROPS		Yes	
Cabin Option		Yes	
TYRES			
			
Radial Agri: Front Rear 6.5/80-12 280/70 R18	Turf: Front Rear 23x8.50-12 33x15.5-16.5	Ind: Front Rear 23x8.50-12 33x15.5-16.5	Galaxy Pro 220/55R12 280/70R16
Front loader		YES optional	

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com