

Solis

THE TOUGHEST
PERFORMER
FOR YOUR FIELD

S 90
SHUTTLE XL



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR

THE TOUGHEST PERFORMER FOR YOUR FIELD

S90
SHUTTLEXL

Solis



FEATURES		S90 SHUTTLEXL
ITL ENGINE		
No. of Cylinders / Capacity (cc) / Emissions Level	4/ 4087/ CRDi Stage V	
After Treatment System	DOC + DPF + SCR (Ad Blu)	
Rated Engine Power (kw/Hp)	67.3/90	
Rated Engine Speed	2200	
Max. Torque (Nm)	375@1400 Rpm	
Aspiration	Turbo Charged	
Intercooler	●	
Air Cleaner	Dual Stage Dry Type	
Block Heater	○	
Updraft Exhaust Pipe	●	
Downdraft Exhaust Pipe	○	
Fuel Tank Capacity (L)	110	
DEF Tank Capacity (L)	12	
TRANSMISSION		
12x12 Synchro Shuttle Transmission (4WD)	●	
Minimum Forward Speed	1.22kmph	
Maximum Forward Speed	35kmph	
20x20 Synchro Shuttle Transmission (4WD) with Super Creeper	○	
Minimum Forward Speed	0.25kmph	
Maximum Forward Speed	40kmph	
FRONT AXLE		
4WD Front Axle	●	
Differential Lock	Mechanical	
4WD Actuation	Electro Hydraulic	
Brake Actuation	Hydraulic Assisted	
PTO		
PTO Type	Mechanical	
540/540E	●	
540/1000	○	
540/Ground Speed	○	
HYDRAULIC		
Hydraulic Pump Flow (LPM)	65	
Draft Control	●	
Liftomatic System	●	
Lift Capacity	3000 Kg / 3500 Kg (0)	
Linkage Category	II	
Self Locking Linkages	○	
Max. no. of Rear Remotes	2/3 (0)	
Max. no. of Mid Remotes	○	

● Standard ○ Optional

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

FEATURES		S90 SHUTTLEXL
Mechanical Joystick Control for Mid Mounts with Valves	○	
REAR HITCHES		
E-Mark Swinging Drawbar	●	
Semi Automatic Ladder Hitch	○	
Automatic Ladder Hitch	○	
Cuna Type Ladder Hitch	○	
TRAILER BRAKES		
Without Trailer Brakes	●	
Hydraulic Trailer Brakes	○	
Dual Line Pneumatic Trailer Brakes	○	
ELECTRICALS (ROPS/CAB)		
Battery	130AH 800CCA	
Alternator	120A	
Button Operated Battery Cut off Switch, 3 Pinsocket, Seven on Trailer Socket	●	
OPERATOR ENVIRONMENT		
Suspended Platform (with ROPS)	●	
Premium Driver Seat	○	
Tiltable & Telescopic Steering	○	
Integrated Loader Joystick	○	
Cabin Air Conditioning (with Cabin)	○	
DIMENSIONS (ROPS/CAB)		
Wheelbase (mm)	2350	
Overall Height (mm)	2700-2720	
Overall Width (mm)	2030-2050	
Overall Length (mm)	3985-4205	
Front Track Width (mm)	1675	
Rear Track Width (mm)	1510	
Ground Clearance (mm)	370	
Unladen Mass (Kg)	4035	
Tyre Combination	12.4x24 & 18.4x30	
OPTIONAL TYRE COMBINATIONS		
Bias Tyres (4WD)	13.6*24 16.9*34	
Radial Tyres (4WD)	320/85R24 & 460/85R30 320/70R24 & 480/70R30 360/85R24 & 460/85R30 420/65R24 & 540/65 R34	

DEALER STAMP

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com