

SOLIS

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

26
SHUTTLE^{XL}



INTEGRATED
LOADER
JOYSTICK (OPTIONAL)

MULTI TIRE OPTIONS
(AGRI, INDUSTRIAL
& TURF TYRE)

QUICK ATTACHED
LOADER

SYNCHROMESH
SHUTTLE

9 FORWARD
X 9 REVERSED GEAR



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR



26
SHUTTLEXL

Solis



FEATURES 26 SHUTTLEXL (9+9)	
ENGINE	
Engine Type	3-Cylinder Diesel Engine
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the Engine Compartment, Downward Discharge
TRANSMISSION	
Drive	4WD
Clutch	Single Clutch
Gearbox	9 Forward + 9 Reverse
Front Axle	4WD
Transmission	Constant Mesh with Synchromesh Shuttle Lever
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	21.46 @2760 fly up
Minimum Speed (Km/Hr)	1.14@rated
BRAKES	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Yes, Foot Operated
PTO	
PTO (RPM)	540/540E
PTO (Actuation)	Mechanical
STEERING	
Steering	Power Steering
ELECTRICAL	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional Hydraulic Circuit	1 DA
Hydraulic Lifting Capacity (Kg)	775*
Lift Rods	Standard
Litre Per Minute (LPM)	17.8
SAFETY SWITCH	
PTO Safety	Standard

FEATURES 26 SHUTTLEXL (9+9)	
Neutral Safety Switch	Standard
Clutch Safety Switch	Standard
CAPACITY (LTRS)(+/-5%)	
Fuel Tank (Ltr.)	20
TURNING RADIUS	
Without Brakes (m) as per Standard Tyres	3.02 (RHS), 3.15 (LHS)
TYRE	
Front	6.00-12
Rear	8.30-20
DIMENSION & WEIGHT(+/-5%)	
Weight (Kg)	1250
Wheel Base (mm)	1570
Total Length (mm)	2895
Total Width (mm)	1215 (max)-1050 (min)
Height (mm) Up to ROPS	2325
Min Ground Clearance (mm)	240
Front Track (mm)	885
Rear Track (mm)	960
OTHERS	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard
Front & Rear Weights with Std. Ballast	Front Weights-2 x 15
Trailer Hitch	Towbar, Drawbar (Optional)
ROPS	Yes
OPTIONAL FEATURES	
Cabin Option	Optional Only Heater
TYRES	
 Radial Agri: Front Rear 6.5/80-12 280/70 R18	 Turf: Front Rear 25x8,50-14 13.60-16
 Ind: Front Rear 23x8,50-12 33x15,50-16,5	 Galaxy Pro R- 280/70R16
Front loader	Yes Optional

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com