

Solis

5

AMONG TOP **5 TRACTOR**
MANUFACTURERS
GLOBALLY

1

NO. 1 TRACTOR
EXPORTER FROM
INDIA



EMINENT PRESENCE
IN **150+ COUNTRIES**



WORKFORCE OF
6000+ DEDICATED EMPLOYEES
WITH 500+ ENGINEERS IN R&D



JOINT VENTURE
WITH **YANMAR**
(JAPAN)



Solis

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | **Work:** Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | **Phone:** +91-01882-522220/ 522221

Fax: +91- 01882-522222 | **Email:** info@solisworld.com | **URL:** www.solistractors.com

Follow us on:

f www.facebook.com/SolisTractors/ | www.twitter.com/SolisTractor | www.linkedin.com/company/solis-tractors-international

www.instagram.com/solis_tractors | www.youtube.com/c/SolisTractors



A COMPACT RANGE

THAT DEFIES LIMITS



www.solistractors.com



INTRODUCING

Solis Compact Series

Solis compact tractors combine advanced technology and durability in their design to deliver maximum productivity to small and hobby farms. Available in 16 - 26 HP options, these tractors are engineered for efficiency, eco-friendliness, and consistent performance, offering exceptional value in a compact form. Designed for today's hobby farmers, landscapers, and small landowners, Solis compact series excels in tight spaces without compromising power.

16

20+

22

26+

26
EXTRA

26
SHUTTLE XL
EXTRA

YOUR GARDEN'S NEW PRODUCTIVITY PARTNER

S16



KEY FEATURES



3 Cylinder
Stage "V"
S-Tech Engine



6F+2R
Transmission



Sleek & Stylish
Bonnet



Hydraulic Lifting
Capacity 500 Kg



Spacious
Operator Area



Heavy Duty
Front Axle

01 WORKABILITY

Powerful ITL 3-Cylinder Stage V Engine- S16 is powered by a reliable ITL 3-cylinder engine, built for high performance, superior fuel efficiency, and reduced emissions. It delivers robust power to tackle a wide range of agricultural tasks with ease.

Efficient Lifting Capacity & Hydraulic System- With a strong 500 kg lifting capacity and a high-efficiency hydraulic pump, S16 effortlessly handles heavy-duty implements. It ensures smooth and reliable operation, making it a trusted ally in the field.

Heavy Duty Front Axle- Designed to conquer rough terrains and carry heavy loads with ease, delivering unmatched stability, strength, and smooth operation.



03 ALL-DAY COMFORT

S-Comfort Package - Solis S16 is designed to enhance your overall operating experience with an ergonomically designed operator area. It ensures smooth and comfortable task performance with a focus on convenience.

Modern Styling & Enhanced Visibility- A sleek 100% metal bonnet not only adds a modern touch but also aids in improved engine cooling. Twin projector headlamps provide superior visibility, ensuring safe operation even in low-light conditions.



02 OPERABILITY

Advanced Transmission- Equipped with a 6 forward + 2 reverse transmission, the S16 offers smooth gear shifts and superior traction across varying terrains, delivering better control and productivity on every job.

Low Maintenance- Built for longevity, the S16 requires minimal upkeep while delivering consistent performance, reducing downtime and keeping operating costs low.



04 OPTIONAL FEATURES

Tyre Options- Choose from a wide selection designed to match every terrain and task, offering superior grip and smoother rides across all conditions.

Front Loader (Optional)- Enhance your tasks with added power using this versatile attachment, ideal for lifting, loading, and handling materials with ease.





SPECIFICATIONS



FEATURES	S16
ENGINE	
Engine Type	ITL 3 Cylinder
HP Category	16
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	979
Rated RPM (+/-25mm)	2700
Air Cleaner	Dry with clogging sensor
Cold Start	Standard
Max Torque (Nm)	48
Exhaust	Silencer in the engine compartment, downward discharge
TRANSMISSION	
Drive	4 WD
Clutch	Single Clutch
Gearbox	6 Forward + 2 Reverse
Front Axle	4WD
Transmission	Sliding Mesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	15.1@2950
Minimum Speed (Km/Hr)	1.36@rated
BRAKES	
Brakes	Dry drum brakes
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Yes, Foot Operated
PTO	
PTO (rpm)	540, 1000
PTO (actuation)	Mechanical
STEERING	
Steering	Mechanical
ELECTRICAL	
Battery	12V, 60 Ah
Alternator	12V, 36 A
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional hydraulic circuit	1 DA

FEATURES		S16	
Hydraulic Lifting Capacity		500 Kg	
Lift Rods		Standard	
Litres Per Minute (LPM)		13	
SAFETY SWITCH 			
PTO Safety		Standard	
Neutral Safety Switch		Standard	
Clutch Safety Switch		Standard	
CAPACITY (LTRS)(+/-5%) 			
Fuel Tank (Lit)		26	
TURNING RADIUS 			
Without brakes (m) as per standard tyres		2.7(RHS) & 2.9(LHS)	
TYRE 			
Front		5.00-12	
Rear		8.00-18	
DIMENSION & WEIGHT(+/-5%) 			
Weight (Kg)		980	
Wheel Base (mm)		1420	
Total Length (mm)		2735	
Total Width (mm)		945 (max) - 940 (min)	
Height (mm) Up to ROPS		1945	
Min Ground Clearance (mm)		200	
Front Track (mm)		805	
Rear Track (mm)		715	
OTHERS 			
Fuel Indicator Gauge		Standard	
Front Tow Hook		Standard	
Front & Rear Weights with std. Ballast		Front weights 30 Kg - 2 x 15 Kg	
Trailer Hitch		1. E-marked swinging drawbar	
		2. Clevis Hitch	
		3. Semi-Automatic hitch	
ROPS		Yes	
OPTIONAL FEATURES 			
TYRES			
			
Radial Agri: Front Rear	Turf: Front Rear	Ind: Front Rear	Galaxy Pro: Front Rear
6.5/80-12 280/70 R18	23x8.50-12 33x15.5-16.5	23x8.50-12 33x15.5-16.5	220/55R12 280/70R16
Additional Tyre		Front Tyre - 6.00-12 Rear Tyre - 8.30-20	
Front Loader		YES optional	

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development.

POWERING A NEW ERA OF EFFICIENT AGRICULTURE

S20+



KEY FEATURES



**3 Cylinder
Mitsubishi
Engine**



**6F+2R
Sliding Mesh
Transmission**



**Power
Steering**



**Hydraulic Lifting
Capacity 500 Kg**



**Side Shift
Gear Lever**



**Heavy Duty
Front Axle**



**Radial Agri, Wider Agri,
Industrial, Turf Tyre
Options**

01 WORKABILITY

Power-Packed Mitsubishi Engine- Solis S20+ is powered by a robust 3-cylinder Mitsubishi engine that delivers a reliable 20 HP output. Engineered for consistent performance across diverse terrains, it's built to handle mid-range agricultural tasks with ease.

High Lifting Capacity & Hydraulic Efficiency- Equipped with a powerful 500 kg lifting capacity and efficient high hydraulic pump flow, the auxiliary circuit ensures responsive hydraulic performance for uninterrupted productivity.

Heavy Duty Front Axle- It offers superior durability, load-bearing strength, and seamless performance in harsh conditions.



03 ALL-DAY COMFORT

S-Comfort Package- Designed for long working hours, the S20+ features an ergonomic operator area with a comfortable seat and a conveniently positioned side-shift gear lever, ensuring smooth and fatigue-free operation.

Tough and Stylish- A sleek, 100% metal bonnet not only enhances the tractor's aesthetics but also facilitates easy access during maintenance. Advanced twin projector headlamps enhance visibility in low-light conditions, adding a modern and bold look that combines safety with style.



02 OPERABILITY

Smooth Mechanical 6F+ 2R Transmission- The mechanical transmission system ensures accurate speed control and efficient power delivery for various operations. The side-shift gear lever enhances operator ease with quicker gear transitions and reduced fatigue during long hours.

Reinforced Safety for Rugged Use- Built for durability, the Solis S20+ features a sturdy frame and reinforced safety platform that offers added protection in demanding working conditions, delivering peace of mind in every operation.



04 OPTIONAL FEATURES

Tyre Options- Our diverse tyre range lets you choose the perfect fit for stability, traction, and comfort in every application.

Front Loader (Optional)- This transforms your tractor into a versatile machine for smooth material handling and load management.





BUILT FOR THE EXTRAORDINARY

SPECIFICATIONS



FEATURES	20+
ENGINE	
Engine Type	3 Cylinder (Water Cooled) Engine
HP Category	20
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	953
Rated RPM	2700
Air Cleaner	Dry with clogging sensor
Cold Start	Standard
Max. Torque (Nm)	52
Exhaust	Silencer in the engine compartment, downward discharge
TRANSMISSION	
Gear Shifting	Center shift (std.), Side shift (opt.)
Drive	4WD
Clutch	Single Clutch
Gearbox	6 Forward + 2 Reverse
Front Axle	4WD
Transmission	Sliding Mesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	15.1@2900
Minimum Speed (Km/Hr)	1.36@rated
BRAKES	
Brakes	Oil Bath Brake
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential lock	Yes, Foot Operated
PTO	
PTO (rpm)	540, 1000
PTO (Actuation)	Mechanical
STEERING	
Steering	Power Steering
ELECTRICAL	
Battery	12 V, 60 Ah
Type of Actuation	12V, 36 A
Parking Brake	Standard

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development.

FEATURES		20+	
HYDRAULICS 			
3 Point Linkage		Cat 1 - N	
Stay Bars		Anchor Chain	
Auxiliary Hydraulic Circuit		1DA	
Lift Rods		Standard	
Lifting Capacity (Kg)		500	
Litre Per Minute (LPM)		13.3	
SAFETY SWITCH 			
PTO Safety		Standard	
Neutral Safety Switch		Standard	
Clutch Safety Switch		Standard	
CAPACITY (LITRE) (+/-5%) 			
Fuel Tank (Ltr.)		26	
TURNING RADIUS 			
Without Brakes (m)		3.2(RHS), 3.3(LHS)	
TYRE (STANDARD) 			
Front		6*12	
Rear		8.3*20	
DIMENSION & WEIGHT (+/-5%) 			
Weight (kg)		970	
Wheel Base (mm)		1425	
Total Length (mm)		2735	
Total Width (mm)		945(max)-940(min)	
Height (mm) Up to ROPS		1945	
Min. Ground Clearance (mm)		200	
Front Track (mm)		805	
Rear Track (mm)		715	
OTHERS 			
Fuel Indicator Gauge		Standard	
Front Tow Hook		Standard	
Front & Rear Weights with Std. Ballast		Front weights 30 Kg - 2 x 15 Kg	
Trailer Hitch		1. E-marked swinging drawbar 2. Clevis Hitch 3. Semi-Automatic hitch	
ROPS		Yes	
Cabin Option		Yes	
TYRES			
			
Radial Agri: Front Rear	Turf: Front Rear	Ind: Front Rear	Galaxy Pro: Front Rear
6.5/80-12 280/70 R18	23x8.50-12 33x15.5-16.5	23x8.50-12 33x15.5-16.5	220/55R12 280/70R16
Front Loader		YES optional	



EFFICIENCY THAT FITS ANYWHERE

KEY FEATURES

- 

Xtra Efficient Stage V 3 Cylinder Engine
- 

6F+2R Sliding Mesh Transmission
- 

Hydraulic Lifting Capacity 600 Kg
- 

Twin Projector Lamps
- 

Spacious Operator Area
- 

Heavy Duty Front Axle

01 WORKABILITY

Fuel-Efficient High-Performance Engine- Solis S22 features a powerful ITL-built Stage V engine, engineered for fuel efficiency and dependable performance across a wide range of agricultural and utility tasks.

Robust Lifting Capacity & Hydraulic System- With a lifting capacity of 600 kg, the Solis S22 effortlessly handles implements. Its reliable hydraulic system ensures smooth operation and increased productivity in the field.

Heavy Duty Front Axle- This rugged front axle ensures enhanced balance, reliability, and smoother rides even on challenging surfaces.



03 ALL-DAY COMFORT

Modern Bonnet Design- The Solis S22 boasts a sleek bonnet that not only enhances its modern styling but also improves air circulation for superior engine cooling.

Advanced Lighting System- With twin projector headlamps, the S22 delivers clear, focused visibility in low-light conditions, ideal for early mornings and late evenings.



02 OPERABILITY

Efficient Transmission System - Equipped with a 6-speed forward and 2-speed reverse transmission, the S22 offers smooth gear shifting and enhanced control, allowing for versatile performance across various terrains.

Oil-Immersed Brakes for Enhanced Safety - The S22 features oil-immersed brakes that deliver consistent braking power, extended durability, and greater operational safety even during intensive use.



04 OPTIONAL FEATURES

Tyre Options- With multiple tyre choices, you can tailor your tractor's performance to any terrain or workload.

Front Loader (Optional)- With the optional front loader, your tractor is ready for efficient loading, lifting, and daily operational demands.





SPECIFICATIONS

FEATURES	Z2
ENGINE	
Engine Type	ITL Make - GTV BB
HP Category	22
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1130 cc (1.13 ltr)
Rated RPM (+/-25mm)	2700
Air Cleaner	Dry with clogging sensor
Cold Start	Standard
Max Torque (Nm)	55
Exhaust	Silencer in the engine compartment, downward discharge
TRANSMISSION	
Drive	4 WD
Clutch	Single Clutch
Gearbox	6 Forward + 2 Reverse
Front Axle	4WD
Transmission	Sliding Mesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	17.02@2950
Minimum Speed (Km/Hr)	2.13@rated
BRAKES	
Brakes	Oil immersed brakes
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Yes, Foot Operated
PTO	
PTO (rpm)	540, 1000
PTO (actuation)	Mechanical
STEERING	
Steering	Power Steering
ELECTRICAL	
Battery	12V, 65 Ah
Alternator	12V, 36 A
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional hydraulic circuit	1 DA

FEATURES		Z2	
Hydraulic Lifting Capacity		600 Kg	
Lift Rods		Standard	
Litres Per Minute (LPM)		13.7	
SAFETY SWITCH 			
PTO Safety		Standard	
Neutral Safety Switch		Standard	
Clutch Safety Switch		Standard	
CAPACITY (LTRS)(+/-5%) 			
Fuel Tank (Lit)		26	
TURNING RADIUS 			
Without brakes (m) as per standard tyres		3.28 (RHS), 3.15 (LHS)	
TYRE 			
Front		6.00-12	
Rear		8.30-20	
DIMENSION & WEIGHT(+/-5%) 			
Weight (Kg)		1070	
Wheel Base (mm)		1560	
Total Length (mm)		2750	
Total Width (mm)		1075 (max) - 1050 (min)	
Height (mm) Up to ROPS		1940	
Min Ground Clearance (mm)		230	
Front Track (mm)		875	
Rear Track (mm)		830	
OTHERS 			
Fuel Indicator Gauge		Standard	
Front Tow Hook		Standard	
Front & Rear Weights with std. Ballast		Front weights 30 Kg - 2 x 15 Kg	
Trailer Hitch		1. E-marked swinging drawbar 2. Clevis Hitch 3. Semi-Automatic hitch	
ROPS		Yes	
OPTIONAL FEATURES 			
TYRES			
			
Radial Agri: Front Rear 6.5/80-12 280/70 R18	Turf: Front Rear 23x8.50-12 33x15.5-16.5	Ind: Front Rear 23x8.50-12 33x15.5-16.5	Galaxy Pro Front 220/55R12 Rear 280/70R16
Front Loader		YES optional	

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development.

PERFORMANCE YOU CAN COUNT ON

S26+

01 WORKABILITY

Reliable Mitsubishi Engine- The Solis S26+ is powered by a trusted 3-cylinder Stage V Mitsubishi engine, renowned for its durability, strength, and fuel efficiency. It delivers consistent performance across both light-duty and demanding terrains.

Advanced Hydraulic System- With a robust 775 kg lifting capacity and a **19.4 LPM** hydraulic pump flow, the S26+ effortlessly manages heavier implements. Equipped with a hydraulic top link, PC/DC control, and 1DA auxiliary hydraulic circuit, it ensures precision and ease in every operation.

Heavy Duty Front Axle- Engineered for rough terrain, the heavy-duty front axle brings maximum stability and long-lasting performance.



03 ALL-DAY COMFORT

Contemporary Bonnet Design- A modern, sleek 100% metal hood bonnet gives the S26+ a bold visual appeal, ensuring easy access for routine maintenance while offering a smart combination of style and functionality.

Spacious Operator Area- Designed with a wide and comfortable space for the operator, it ensures easier handling and more relaxed working over long hours.



02 OPERABILITY

Smooth Transmission- Featuring a 6F+2R mechanical transmission with a side-shift gear lever, the Solis S26+ enables quick and seamless gear transitions, enhancing control and reducing operator fatigue during extended working hours.

Reinforced Safety for Every Task- Built with strong frames and a secure operator platform, the S26+ prioritises safety. Whether on the farm or at a worksite, it offers dependable protection in all conditions.



04 OPTIONAL FEATURES

Tyre Options- Select from a variety of tyres built for different terrains, ensuring optimal performance and handling every time.

Front Loader (Optional)- The optional front loader adds versatility for material handling, making every task quicker and easier.



KEY FEATURES



3 Cylinder
Mitsubishi
Engine



6F+2R
Transmission



Quick Attach
Loader & Bucket
With 3rd Electric
Function Option



Hydraulic Lifting
Capacity 775 Kg



Side Shift
Gear Lever



Heavy Duty
Front Axle

26+

ADVANCED SIDE SHIFT WITH FOPS

FOR BETTER CONTROL & COMFORT



UPGRADED FEATURES



FOPS with Canopy

The certified Falling Object Protective Structure (FOPS) offers safety to the operator by shielding them from hazards like falling logs, construction debris, or loader materials. The canopy adds extra protection against weather.



OPG (Operator Protective Guards)

An optional safety structure designed to protect the operator from falling objects during loader work or when lifting heavy materials. Ideal for applications involving high stacking or rough handling.



PC/DC (Position Control / Draft Control)

Delivers accurate control over implement positioning and soil depth for optimal performance. Ensures consistent results in every pass for superior field productivity.



Grill Guard

Provides extra protection to the front grill and radiator against external damage and debris. Safeguards critical components for long-lasting tractor health.



Additional Bigger Tyres

Larger tyres ensure better grip, improved traction, and smoother movement across all surfaces. Tackle challenging terrains with confidence and comfort.

* Some features are optional



SPECIFICATIONS

FEATURES	S 26+
ENGINE 	
Engine Type	3 Cylinder Diesel Engine
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry with Clogging Sensor
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the Engine Compartment, Downward Discharge
TRANSMISSION 	
Drive	4WD
Clutch	Single Clutch
Gearbox	6 Forward + 2 Reverse
Front Axle	Heavy Duty
Transmission	Sliding Mesh
SPEED (FORWARD) 	
Maximum Speed (Km/Hr)	16.2@2815 Fly Up
Minimum Speed (Km/Hr)	1.64@2500 rated
BRAKES 	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK 	
Differential Lock	Yes, Foot Operated
PTO 	
PTO (RPM)	540, 1000
PTO (Actuation)	Mechanical
STEERING 	
Steering	Power Steering
ELECTRICAL 	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
HYDRAULICS 	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional Hydraulic Circuit	1DA
Hydraulic Lifting Capacity (Kg)	775
Lift Rods	Standard
Litre Per Minute (LPM)	19.4
Hydraulics Top Link	Standard
High Loader Lifting Capacity (Kg) at Pivot Point	640

FEATURES	S 26+
SAFETY SWITCH 	
PTO Safety	Standard
Neutral Safety Switch	Standard
Clutch Safety Switch	Standard
CAPACITY (LTRS)(+/-5%) 	
Fuel Tank (Lit)	28
TURNING RADIUS 	
Without Brakes (m) as per Standard Tyres	3.18 (RHS), 3.10 (LHS)
TYRE 	
Front	23x8.5-12
Rear	280x70 R18
DIMENSION & WEIGHT(+/-5%) 	
Weight (Kg)	1070
Wheel Base (mm)	1560
Total Length (mm)	2760
Total Width (mm)	1075 (max) - 1055 (min)
Height (mm) Up to ROPS	1955
Min Ground Clearance (mm)	245
Front Track (mm)	885
Rear Track (mm)	835
OTHERS 	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard
Front & Rear Weights with std. Ballast	Front weights - 2 x 15 Kg
Trailer Hitch	Drawbar / Optional Towbar
ROPS	Yes
TYRES	
 Radial Agri: Front Rear	 Turf: Front Rear
 Ind: Front Rear	 Galaxy Pro: Front Rear
6.5/80-12 280/70 R18	23x8.50-12 33x15.5-16.5
Heavy Duty Loader	YES optional

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All dimensions are with standard tyres.

**H26
EXTRA**

THE FUTURE OF ENHANCED POWER PRODUCTIVITY



01 WORKABILITY

Powerful S-TECH Engine- Solis H26 is equipped with a robust 3-cylinder S-TECH engine that delivers dependable performance with exceptional fuel efficiency, perfect for a wide range of farming and utility tasks.

Integrated S-BOOST Hydraulic System- It offers a lifting capacity of 775 kg. With the advanced S-BOOST hydraulic system, 3DA, hydraulic top link, high-flow LPM pump, and PC/DC controls, the H26 handles them all with ease.

Heavy Duty Front Axle- The robust front axle provides unparalleled support and control when navigating heavy loads and uneven terrain.



03 ALL-DAY COMFORT

Cruise Control with Auto Throttle- Cruise Control with Auto Throttle automatically adjusts engine RPM based on hydrostatic pedal input, maintaining consistent speed without manual throttle use. It reduces operator fatigue, improves fuel efficiency, and simplifies loader and large-area operations.

Flat Platform with Premium Seating- Built for comfort, the spacious flat platform allows easy entry and movement. The high-back suspension seat comes with armrests and a headrest, offering ergonomic support and reduced vibration for a fatigue-free ride throughout the day.



02 OPERABILITY

Advanced Hydrostatic Transmission (HST) - The H26 features a dual brake pedal system and top speed of 21 kmph, ensuring effortless control and superior manoeuvrability.

Mid & Rear PTO for Versatile Performance- With both mid and rear PTO options and a foldable PTO guard, the Solis H26 supports a wide range of agricultural and landscaping implements, making it an all-rounder for diverse applications.



04 OPTIONAL FEATURES

Tyre Options- A broad range of tyre options to give you the edge, whether you need firm traction or a smooth cruise.

Front Loader (Optional)- Boost functionality for heavy-duty tasks like loading and lifting, increasing your tractor's versatility on the job.





H26
EXTRA

ENGINEERED FOR THE HEAVY LIFTERS

KEY FEATURES



3 Cylinder
Diesel
Engine



Separate Pedal
For Forward
& Reverse



Heavy Duty
Front Axle



Hydraulic Lifting
Capacity 775 Kg



High Loader Lifting
Capacity 640 Kg

UPGRADED FEATURES



C Type Charger

Charge your mobile devices and accessories on the go, so you're always powered up.



Higher LPM pump

Experience faster lifting and smoother hydraulic operations for improved productivity.



Hydraulics Top Link

Adjust implement angles precisely for better control and field performance.



3DA

Enables multi-directional hydraulic flow, allowing for the easy operation of multiple implements.



FOPS with Canopy

Protects against falling objects and provides shade from the sun or rain.



OPG (Operator
Protective Guards)

Shields from dust, debris, and branches—ideal for rough and off-road conditions.



ROPS lights

Built-in lights on ROPS ensure safe operation during low-light hours.



Canopy lights

Illuminates the work area under the canopy during early mornings or late evenings.



Bluetooth Speakers

Enjoy music or hands-free calls during long work hours.



Auto Throttle

Automatically adjusts engine speed based on load, saving fuel and reducing fatigue.



Grill Guard

Protects the grill and radiator from mud, stones, and debris, extending equipment life.



Foldable
PTO Guard

Ensures safety with flexibility—folds away easily for maintenance or implementation of change.



PC/DC (Position Control /
Draft Control)

Automatically adjusts implement height for precise and efficient ploughing.



Mid ROPS

Sturdy mild steel frame enhances operator safety in rollover situations.



Wireless Charger

Charge devices wirelessly—no cables, no clutter.



Additional
Bigger Tyres

Provides better grip, ride comfort, and stability on uneven terrains.



HVAC

Stay cool in summer and warm in winter with all-season comfort in your cabin.

* Some features are optional



SPECIFICATIONS

FEATURES	H26
ENGINE 	
Engine Type	3-Cylinder Diesel Engine
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry with clogging sensor
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the engine compartment, downward discharge
TRANSMISSION 	
Drive	4WD
Clutch	Wet type clutch for PTO
Gearbox	Hydrostatic
Front Axle	4WD
Transmission	HST (Hydrostat)
SPEED (FORWARD) 	
Maximum Speed (Km/Hr)	21.03@2660
Minimum Speed (Km/Hr)	3.18 at low idle 900 erpm, 8.83@rated erpm
BRAKES 	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK 	
Differential Lock	Yes, Foot Operated
PTO 	
PTO (rpm)	Mid PTO- 2100 RPM, Rear 540
PTO (actuation)	Electro hydraulic operated/mechanical selector lever
STEERING 	
Steering	Power steering
ELECTRICAL 	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
HYDRAULICS 	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Hydraulic Lifting Capacity (Kg)	775
Lift Rods	Standard
Litre Per Minute (LPM)	20
High Loader Lifting Capacity (Kg)	640
SAFETY SWITCH 	
PTO Safety Switch	Standard
Neutral Safety Switch	Standard
Clutch Safety Switch	Standard

FEATURES		H26	
CAPACITY (LTRS)(+/-5%) 			
Fuel Tank (Lit)		22	
TURNING RADIUS 			
Without brakes (m) as per standard tyres		3.05 (RHS), 2.62 (LHS)	
TYRE 			
Front		6.00-12	
Rear		8.30-20	
DIMENSION & WEIGHT(+/-5%) 			
Weight (Kg)		1235	
Wheel Base (mm)		1570	
Total Length (mm)		2895	
Total Width (mm)		1215 (max)-1050 (min)	
Height (mm) Up to ROPS		2325	
Min Ground Clearance (mm)		240	
Front Track (mm)		885	
Rear Track (mm)		960	
OTHERS 			
Fuel Indicator Gauge		Standard	
Front Tow Hook		Standard	
Front & Rear Weights with std. Ballast		Front weights - 2 x 15 Kg	
Trailer Hitch		1. E-marked swinging drawbar 2. Clevis Hitch 3. Semi-Automatic hitch	
ROPS		Yes	
C - Type Charger		Yes	
FOPS		Yes	
OPG (with loader)		Optional	
Hydraulics Top Link		Standard	
Additional Hydraulic Circuit		3DA	
USB Charger		Yes	
PC/DC		Yes	
Wireless Charger		Yes	
ROPS Lights		Yes	
Bluetooth Speaker		Yes	
Mid ROPS		Yes	
OPTIONAL FEATURES 			
Cabin Option		Yes	
TYRES			
			
Radial Agri: Front Rear	Turf: Front Rear	Ind: Front Rear	Galaxy Pro: Front Rear
6.5/80-12 280/70 R18	25x8,50-14 13.60-16	23x8,50-12 33x15,50-16,5	220/55R12 280/70R16
Front Loader		YES optional	

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

COMPACT POWER FOR ALL TERRAINS

S26
SHUTTLE XL
EXTRA



KEY FEATURES



3 Cylinder
Diesel
Engine



9F+9R Constant
Mesh With
Synchronesh
Shuttle Lever



Hydraulic Lifting
Capacity 775 Kg



High Loader
Lifting Capacity
640 Kg



Integrated
Loader Joystick
(optional)



Heavy Duty
Front Axle

01 WORKABILITY

High-Performance Mitsubishi Diesel Engine- Solis S26 Shuttle XL is equipped with a reliable 3-cylinder Mitsubishi diesel engine, renowned for its robust performance, exceptional fuel efficiency, and consistent, dependable operation in all conditions.

Efficient Hydraulic System with Superior Lifting Capacity- Engineered for performance, the advanced hydraulic system features a lifting capacity of 775 kg and a hydraulic top link for improved implement control. With a high flow rate of 20 LPM, the 3DA system and PC/DC controls ensure quick response across applications.

Heavy Duty Front Axle- The heavy-duty front axle enhances durability, load capacity, and smooth handling in the most demanding environments.



03 ALL-DAY COMFORT

S Comfort Package- Designed with operator well-being in mind, the S Comfort Package includes an ergonomic layout, spacious platform, and premium seating. Together, they ensure reduced fatigue and a smooth ride throughout long working hours.



02 OPERABILITY

Synchronesh Shuttle Transmission - The S26 Shuttle XL is equipped with a smooth synchronesh shuttle transmission offering 9 forward and 9 reverse gears. Paired with a top speed, it provides better control, seamless directional changes, and optimal speed for various tasks.



04 OPTIONAL FEATURES

Tyre Options- Our wide range of tyres ensures the ideal match for any surface, delivering comfort, control, and power where you need it.

Front Loader (Optional)- Expand your tractor's role with this efficient tool for everyday material handling, designed for both strength and convenience.



VERSATILE COMPANION IN EVERY FIELD



26
SHUTTLE XL
EXTRA

UPGRADED FEATURES



C Type Charger

This enables fast and hassle-free charging of mobile devices directly from the tractor.



Higher LPM pump

Boosts hydraulic oil flow for faster implement lifting and operation, enhancing efficiency in every task.



Hydraulics Top Link

Offers precise tilt and levelling control of implements, ensuring better field finish, uniformity, and stability.



3DA

Facilitates hydraulic movement in three directions, ideal for operating modern, multifunctional implements with ease.



FOPS with Canopy

Combines a Falling-Object Protective Structure with a robust canopy to safeguard the operator against impacts and harsh weather.



OPG (Operator Protective Guards)

Reinforced protective frame around the operator seat that shields against accidental bumps and mechanical hazards.



ROPS lights

Integrated lights on the ROPS structure ensure clear visibility and safer operation in low-light or night-time conditions.



Canopy lights

Strategically placed lights under the canopy illuminate the operator area for safer.



Bluetooth Speakers

Enables wireless music streaming and hands-free calling throughout the day.



Mobile Charger

Dedicated charging port to keep your phone powered during long work hours.



Grill Guard

A protective shield for the front grill and radiator, preventing damage from mud, debris, and flying stones.



Foldable PTO Guard

A practical safety cover for the PTO shaft that folds away easily during attachment or maintenance.



PC/DC (Position Control / Draft Control)

Provides intelligent implementation of height adjustments based on soil conditions.



Mid ROPS

This mid-mounted ROPS offers critical operator safety during rollovers or accidents.



Wireless Charger

Modern wireless charging pad for smartphones offering seamless convenience.



Additional Bigger Tyres

Wider and larger tyres increase traction and stability, perfect for heavy loads.



HVAC

Keeps the cabin comfortable all year long by maintaining the right temperature.

* Some features are optional



POWER THROUGH EVERY WEATHER

SPECIFICATIONS

FEATURES	26 SHUTTLE XL (9+9)
ENGINE	
Engine Type	3-Cylinder Diesel Engine
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the Engine Compartment, Downward Discharge
TRANSMISSION	
Drive	4WD
Clutch	Single Clutch
Gearbox	9 Forward + 9 Reverse
Front Axle	4WD
Transmission	Constant Mesh with Synchromesh Shuttle Lever
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	21.46@2760 fly up
Minimum Speed (Km/Hr)	1.14@rated
BRAKES	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Yes, Foot Operated
PTO	
PTO (RPM)	540/540E
PTO (Actuation)	Mechanical
STEERING	
Steering	Power Steering
ELECTRICAL	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Hydraulic Lifting Capacity (Kg)	775*
Lift Rods	Standard
Liter Per Minute (LPM)	20
High Loader Lifting Capacity (Kg) at Pivot Point	640
SAFETY SWITCH	
PTO Safety	Standard

FEATURES		S 26 SHUTTLE XL (9+9)	
Neutral Safety Switch		Standard	
Clutch Safety Switch		Standard	
CAPACITY (LTRS)(+/-5%) 			
Fuel Tank (Ltr.)		22	
TURNING RADIUS 			
Without Brakes (m) as per Standard Tyres		3.02 (RHS), 3.15 (LHS)	
TYRE 			
Front		6.00-12	
Rear		8.30-20	
DIMENSION & WEIGHT(+/-5%) 			
Weight (Kg)		1250	
Wheel Base (mm)		1570	
Total Length (mm)		2895	
Total Width (mm)		1215 (max)-1050 (min)	
Height (mm) Up to ROPS		2325	
Min Ground Clearance (mm)		240	
Front Track (mm)		885	
Rear Track (mm)		960	
OTHERS 			
Fuel Indicator Gauge		Standard	
Front Tow Hook		Standard	
Front & Rear Weights with Std. Ballast		Front Weights-2 x 15	
Trailer Hitch		Towbar, Drawbar (Optional)	
ROPS		Yes	
C - Type Charger		Yes	
FOPS		Optional	
OPG (with loader)		Optional	
Hydraulics Top Link		Standard	
Additional Hydraulic Circuit		3DA	
USB Charger		Yes	
PC/DC		Yes	
Wireless Charger		Yes	
ROPS Lights		Yes	
Bluetooth Speaker		Yes	
Mid ROPS		Yes	
OPTIONAL FEATURES 			
Cabin Option		Optional Only Heater	
TYRES			
			
Radial Agri: Front Rear 6.5/80-12 280/70 R18	Turf: Front Rear 25x8,50-14 13.60-16	Ind: Front Rear 23x8,50-12 33x15,50-16,5	Galaxy Pro: Front Rear R- 280/70R16
Front Loader		Yes Optional	

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

GENUINE SPARES FOR LASTING EFFICIENCY



MINOR MAINTENANCE KIT

16 - 26 (6+2 & 9+9)

26 HST

Engine Lube Filter
Part No. - 803007059A
Replace at 50 hours and then at every 250 hours of operation annually

50 HOURS

Fuel Filter
Part No. - 703008219A
Replace at 50 hours and then at every 250 hours of operation annually

250 HOURS



Lube Filter
Part No. - 803007059A
Replace at 50 hours and then at every 250 hours of operation annually

50 HOURS

Fuel Filter
Part No. - 7030082198
Replace at 50 hours and then at every 250 hours of operation annually

250 HOURS

Oil Filter for HYD. Suction Side
Part No. - 10004704AE
Replace at 50 hours and then at every 250 hours of operation annually

250 HOURS

Hydraulic Filter Spin On Delivery Side
Part No. - 300123472A
Replace at 50 hours and then at every 250 hours of operation annually

250 HOURS



MAJOR MAINTENANCE KIT

16 - 26 (6+2 & 9+9)

26 HST

Engine Lube Filter
Part No. - 803007059A
Replace at 50 hours and then at every 250 hours of operation annually

50 HOURS

Fuel Filter
Part No. - 703008219A
Replace at 50 hours and then at every 250 hours of operation annually

250 HOURS

Hydraulic Strainer 160 Micron
Part No. - 10004704AE
Replace after 750 hours annually

750 HOURS

Primary Element Dry Air Cleaner 5 Inch
Part No. - 10055911AA
Replace after every 750 hours annually

750 HOURS



Lube Filter
Part No. - 803007059A
Replace at 50 hours and then at every 250 hours of operation annually

50 HOURS

Fuel Filter
Part No. - 7030082198
Replace at 50 hours and then at every 250 hours of operation annually

250 HOURS

Oil Filter for HYD. Suction Side
Part No. - 10004704AE
Replace at 50 hours and then at every 250 hours of operation annually

250 HOURS

Hydraulic Filter Spin On Delivery Side
Part No. - 300123472A
Replace at 50 hours and then at every 250 hours of operation annually

250 HOURS

Primary Element Dry Air Cleaner 5 Inch (P)
Part No. - 10055911AA
Replace after every 750 hours annually

750 HOURS

Magnetic Strainer Assy
Part No. - 20005340AA
Replace after every 750 hours annually

750 HOURS