

# MB PLOUGH



## SALIENT FEATURES

- The plough is made from boron steel body
- Height adjustable drawbar
- Adjustment for working depth

# MB PLOUGH

MB Plough is used for initial soil preparation for sowing seed or planting. Generally used for deep tillage of land, to help turn over the upper layer of the soil, bringing fresh nutrients to the surface, while burying weeds and remains of previous crop. It also aerates the soil, allows it to hold moisture better and is tough to withstand heavy loads.

## TECHNICAL SPECIFICATIONS

Model Name	Furrow	Frame (mm)	Draw Bar Rod (mm)	Tines (mm)	Length (mm)	Height (mm)	Mould Board (mm)	Bar Point	3 Point Linkage Lever & Connecting Rod (mm)	Width Of Cut (mm)	Weight (Kg. approx)	Tractor Power (HP)
SL-MP-02 MINI	2	72X72 Square Bar	45 (Solid Rod)	28mm Profile Cutting	1008	812	6	Sq 32	65 x 16 (Flat) & 42.6 Round Pipe	400	120	20-26
SL-MP-02	2	80 x 80 x 5 (SQ. Tubular Frame)	50 (Solid Rod)	36mm profile cutting, single piece	1032	1138.5	10			600	290	45+
SL-MP-03	3				1694	1138.5	10			890	400	50+
SL-MP-04	4				2307	1138.5	10			1190	510	60+



ROBUST FRAME



HEAVY DUTY FURROW



LONG LASTING HEAVY DUTY BLADE & BAR POINT



HEAVY DUTY 3 POINT LINKAGE



HEAVY DUTY FRAME

HEAVY DUTY 3 POINT LINKAGE

HIGH TENSILE FASTENERS

HEAVY DUTY TYNE MADE OF EN9 MATERIAL

# SOLIS

## INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)  
 Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 302220, 302221  
 Fax: +91 1882 302293 | Email: exports@sonalika.com | URL: www.solistractors.com

Auth. Dealer