

# **DISC HARROW**

TRAILED TYPE DISC HARROW & HYDRAULIC DISC HARROW

## **SALIENT FEATURES**

- Heavy duty disc to absorb sudden impact
- Sealed bearing increases life & reduces maintenance
- Heavy duty reinforced pipe frame
- Robust bearing hub mechanism & bearings
- Superior powder coated paint

## TRAILED TYPE DISC HARROW & HYDRAULIC DISC HARROW

Disc harrow is used to till the soil where crops are to be planted. It is also used to chop up unwanted weeds or crop remainders. The discs are also offset so that they are not parallel with the overall direction of the implement. This arrangement ensures that the discs will repeatedly slice any ground to which they are applied, in order to optimize the result. The concavity of the discs as well as their offset angle causes them to loosen and lift the soil that they cut.

#### **TECHNICAL SPECIFICATIONS**

	Mode <b>l</b> Name	Model	No. of Disk	S S S S S S S S S S S S S S S S S S S	Frame Size (mm)	Gang Shaft (mm)	Disc Diameter (mm)	Type of Disc	Bearing Hubs	Hydraulic Jack	<b>O</b> Tyre	Weight (Kg. approx.)	Tractor Power (HP)
S	SL-THD-10	10X10	20	SPLIT GANG	Heavy Duty Tube 6 mm	Square Solid Bar 40 mm	660 mm X 6mm	Notched in front & pain in Rear	8 Nos. S.G. Iron (500/7)	Double Action Hydraulic Jach with Hoses & Coupling	Wider Tubeless Tyre	1780	75+
S	SL-THD-12	12X12	24									1970	90+
S	SL-THD-14	14X14	28									2190	105+
SL	L-THD-10-H	10X10	20		132 mm Square	Square Solid Bar 32 mm	610 mm X 5mm		Taper Roller Bearing			1270	60+
SL	L-THD-12-H	12X12	24									1400	80+
SL	L-THD-14-H	14X14	28									1510	95+
SL	L-THD-16-H	16X16	37									1700	110+



THREE BEAM HEAVY STRUCTURE FRAME. HELPS TO PENETRATE IN SOIL EASILY



NOTCHED BLADE HELPS HARROW TO PENETRATE IN FIELD EASILY



IT KILLS OFF UNWANTED CROPS AND REMAINDERS THAT WOULD OTHERWISE HINDER THE GROWTH OF THE WANTED CROPS



HYDRAULICALLY LIFTED
CENTER TYRE
FOR EASE IN
TRANSPORTATION





### INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India) Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 302220, 302221 Fax: +91 1882 302293 | Email: exports@sonalika.com | URL: www.solistractors.com

Auth. Dealer