

ROUND BALER



SALIENT FEATURES

- Robust Pick Up System
- Self Lubricating System
- Sturdy Design
- Safety Slip Clutch for drive overload protection
- Heavy Duty Gearbox

ROUND BALER

SOLIS round baler is suitable to compress all types of windrowed crops with best efficiency. It produces 14-36 kg round bales which can be easily handled. It has a very economical design with best features which makes it apt for baling crops like marsh, hay, cotton, flax and straw easily.

TECHNICAL SPECIFICATIONS

Model Name	Working Width (cm)	Bale Chamber (cm)	Bale Length (cm)	Bale Diameter (cm)	Bale Weight (kg)	Binding Twine	No. of Rollers	Bale Ejection	Lubrication	Efficiency (Bales per hour)	Tractor Forward Speed (km/hr)	Tractor Power (HP)	PTO RPM	Dimension (LxWxH) (cm)	Approx Weight (Kg)	Tyre Size	Drive Protection
SLRB-0.8	80	70	70	50	14-17	Jute Twine / PP	10	Manual / Automatic (Optional)	Central oil lubricating system for chains	60-80	2-5	25-60	540	125x148x116	465	16 x 6.50 - 6 ply - Tubeless	Shear Bolt on Machine. Slip clutch in pickup reel
SLRB-1.15	115	105	105	50	18-22		10							125x180x116	553		
SLRB0.8J	80	70	70	60	24-28		12			40-60				140x148x132	515		
SLRB1.03J	103	93	93	60	28-32		12			140x169x132				580			
SLRB-1.15J	115	105	105	60	32-36		12			140x180x132				620			



STURDY DESIGN



SAFETY SLIP CLUTCH FOR DRIVE OVERLOAD PROTECTION



HEAVY DUTY GEARBOX



HEAVY DUTY FRAME

HIGH TENSILE FASTENERS

SOLIS

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax: +91- 01882-522222 | Email: info@solis.com | URL: www.solistractors.com

Auth. Dealer