

Solis

TRAILER



SALIENT FEATURES

- Heavy duty axle for robust field operations
- Easy to attach and detach with tractor
- Corrugated sheet for better strength
- Optional hydraulic trailer break
- Taper roller bearing used for long durability
- Optional all 4 side openable

TRAILER

Solis trailers have a rugged design to stand up to even the toughest loading and hauling demands under all conditions. The hydraulic unloading and collapsible side panels help to unload the material effortlessly.

TECHNICAL SPECIFICATIONS

Tipping Trailer Single Axle						
Model	SLSTT-1	SLSTT-2	SLSTT-3	SLSTT-5	SLSTT-8	SLSTT-10
Loading Capacity (kg)	1000	2000	3000	5000	8000	10000
Dimension (mm)	2000x1200x355	2130x1370x533	2435x1830x610	3050x1830x610	3650x1830x610	3960x1830x610
Main Chassis (mm)	100x50	100x50	125x65	150x75	200x75	
Floor Sheet (mm)	3			4		
Side Wall Sheet (mm)	2					
Tyre	12/16	600x16	750x16	900x16		
Ring Hitch Dia (mm)	45		50			
Hyd.Cylinder Cap. (Ton)	2	3	10	15	20	
Axle (Break Optional) mm	50	65	75		90	
Axle Bearing	32209 Inner 32209 Outer	32209 Inner 32210 Outer	32213 Inner 32216 Outer			
Weight (Kg)	300	600	915	1250	1550	1800
Tractor Power (HP)	18-26	20-26	35-50	50-70	70-90	90-120

Non Tipping Trailer Single Axle					
Model	SLSNTT-2	SLSNTT-3	SLSNTT-5	SLSNTT-8	SLSNTT-10
Loading Capacity (kg)	2000	3000	5000	8000	10000
Dimension (mm)	2130x1370x533	2435x1830x610	3050x1830x610	3650x1830x610	3960x1830x610
Main Chassis (mm)	100x50	125x65	150x75	200x75	
Floor Sheet (mm)	3		4		
Side Wall Sheet (mm)	2				
Tyre	600x16	750x16	900x16		
Ring Hitch Dia (mm)	45	50			
Axle (Break Optional) mm	65	75		90	
Axle Bearing	32209 Inner 32210 Outer	32213 Inner 32216 Outer			
Weight (Kg)	500	800	1100	1400	1650
Tractor Power (HP)	20-26	35-50	50-70	70-90	90-120














INTERNATIONAL TRACTORS LIMITED












International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | **Work:** Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | **Phone:** +91-01882-522220/ 522221
Fax:+91- 01882-522222 | **Email:** info@solis.com | **URL:** www.solistractors.com

Auth. Dealer

TRAILER

TECHNICAL SPECIFICATIONS

		Tipping Trailer Double Axle Turn Table		
 Model	WTDTT-5	WTDTT-8	WTDTT-10	
 Loading Capacity (kg)	5000	8000	10000	
 Dimension (mm)	3050X1830x610	3650X1830x610	3960X1830x610	
 Main Chassis (mm)	150X75	200X75		
 Floor Sheet (mm)	4			
 Side Wall Sheet (mm)	2			
 Tyre	900X16			
Ring Hitch Dia (mm)	50			
 Hyd Cylinder Cap. (Ton)	15	20		
 Axle (Break Optional) mm	75		90	
 Axle Bearing	32213 Inner 32216 Outer			
 Weight (Kg)	1500	1800	2100	
 Tractor Power (HP)	50-70	70-90	90-120	

		Non Tipping Trailer Double Axle Turn Table		
 Model	WTDNTT-5	WTDNTT-8	WTDNTT-10	
 Loading Capacity (kg)	5000	8000	10000	
 Dimension (mm)	3050X1830x610	3650X1830x610	3960X1830x610	
 Main Chassis (mm)	150X75	200X75		
 Floor Sheet (mm)	4			
 Side Wall Sheet (mm)	2			
 Tyre	900X16			
Ring Hitch Dia (mm)	50			
 Axle (Break Optional) mm	75	75	90	
 Axle Bearing	32213 Inner 32216 Outer		32213 Inner 31216 Outer	
 Weight (Kg)	1350	1650	1950	
 Tractor Power (HP)	50-70	70-90	90-120	



HEAVY DUTY AXLE FOR ROBUST FIELD OPERATIONS



EASY TO ATTACH AND DETACH WITH TRACTOR



CORRUGATED SHEET FOR BETTER STRENGTH



OPTIONAL HYDRAULIC TRAILER BREAK



TAPER ROLLER BEARING USED FOR LONG DURABILITY



OPTIONAL ALL 4 SIDES OPENABLE

Solis

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | **Work:** Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | **Phone:** +91-01882-522220/ 522221

Fax:+91- 01882-522222 | **Email:** info@solis.com | **URL:** www.solistractors.com

Auth. Dealer