

AUTOMATIC POTATO PLANTER



SALIENT FEATURES

- DC motor for Vibration effect in belt for effective planting
- Heavy duty height adjustable axle
- Furrow opener with replaceable wear and tear point and depth adjustable spike
- Rigid and concave shaped mould board for proper ridge formation
- Furrow opener with feeler wheel option

AUTOMATIC POTATO PLANTER

The Automatic Potato Planter is useful in planting potato seeds with incredible singulation, ensuring no two potatoes are buried in a single place. Another advantage with this equipment is uniform depth during the process with the right level of soil compaction resulting in a healthy & greater yield.

TECHNICAL SPECIFICATIONS

Model Name	No. of Rows	No. of Furrow Opener	No. of Ridge Maker	Distance Between Rows (mm)	Working Depth (mm)	Working Width (mm)	Powered By	No. of Cups	Size of Potato Seeds	Fertilizer Tank (Kgs)	No. of Conveyer	Hopper Capacity (Kgs)	Planting Capacity (Acre/Hrs)	Total Length (mm)	Total Width (mm)	Total Height (mm)	Total Weight (Kg Approx)	Potato Planting distance (mm)	Lower Linkage Category	Tractor Power (HP)
SLPPL-2	2	2	3	600 - 660	130 - 150	1320	Wheels	2x34	30-75 (cut or uncut)	75	2	240	1.25	2100	1700	1550	580	100-125-150-175-200-225-250-300	Cat-II	40-60
SLPPL-4	4	4	5			2640		4x34		150	4	420	2.5		3000		880			60-75



RIGID AND CONCAVE SHAPED MOULD BOARD FOR PROPER RIDGE FORMATION



FURROW OPENER WITH REPLACEABLE WEAR & TEAR POINT AND DEPTH ADJUSTABLE SPIKE



WORLD CLASS POWDER COATED PAINT



BORON STEEL SHOVEL



POTATO HOLDING CUPS PROVIDING ZIG ZAG PLANTING



MECHANICAL VIBRATOR

HIGH BUILD QUALITY & RUGGED DESIGN



HELPER'S SEAT

ADJUSTABLE RIDGERS

Solis

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | **Work:** Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | **Phone:** +91-01882-522220/ 522221

Fax:+91- 01882-522222 | **Email:** info@solis.com | **URL:** www.solistractors.com

Auth. Dealer