

HAY RAKE



SALIENT FEATURES

- Durable spring tines made of grade 3 material
- Cam driven maintenance free gearbox
- Rugged design
- Safety guard

HAY RAKE

Solis hay rake is an implement used to make finest quality windrows with minimum contamination with precise action of long arms along with the reduction gearbox. The well structured fluffy windrows helps in making compact bales smoothly. It is designed with superior durability and works efficiently in almost all conditions.

TECHNICAL SPECIFICATIONS

Model Name	Hitching System	Tractor Power (HP)	Max. Working Width (mm)	Number of Rotors	Rotor Diameter (mm)	No. of Arms Per Rotor Unit	Tine Diameter (mm)	Tine Arm Style	Working Speed (km/h)	Standard Tyres	Dimension (LxWxH) (mm)	No of Wheels/Tyres	Weight (kg)
SLR 360/2	CAT-II Standard 3 point hitch	30 & above	3600	1	2700	9	10	Double Coiled & Tangential	2 to 6	13 x 5.00 - 6PR	3600 X 4000 X 1300	2	380
SLR 360/4	CAT-II - 3 point hitch	40 & above		1	2900	9	10	Triangle Profiled Male & Female	2 to 4	16 x 6.5-8 pneumatic tubeless	3600 x 3200 x 1300	4	460



DURABLE SPRING TINES MADE OF GRADE 3 MATERIAL



CAM DRIVEN MAINTENANCE FREE GEARBOX



RUGGED DESIGN



SAFETY GUARD

SAFETY COVER

HEAVY DUTY FRAME



Solis

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | **Work:** Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | **Phone:** +91-01882-522220/ 522221

Fax:+91- 01882-522222 | **Email:** info@solis.com | **URL:** www.solistractors.com

Auth. Dealer