

# SOLIS

— THE TOUGHEST —  
**PERFORMER**  
« FOR YOUR FIELD »

## H26



THERMO DYNAMICS  
BONNET & TWIN  
PROJECTOR LAMPS

HEAVY DUTY  
FRONT LOADER

SEPARATE PEDAL  
FOR FORWARD  
& REVERSE

CRUISE  
CONTROL

LIFTING CAPACITY  
775 KG



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

— Made of —  
**REAL  
STEEL**

**STRATEGIC  
COLLABORATION  
WITH  
YANMAR**














# H26

# Solis



FEATURES	H26
<b>ENGINE</b>	
Engine Type	3-Cylinder Diesel Engine
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry with clogging sensor
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the engine compartment, downward discharge
<b>TRANSMISSION</b>	
Drive	4WD
Clutch	Wet type clutch for PTO
Gearbox	Hydrostatic
Front Axle	Heavy Duty
Transmission	HST (2-Stufen Hydrostat)
<b>SPEED (FORWARD)</b>	
Maximum Speed (Km/Hr)	19.6@2660
Minimum Speed (Km/Hr)	3.18 at low idle 900 erpm, 8.83@rated erpm
<b>BRAKES</b>	
Brakes	Oil Immersed
Type of Actuation	Hydrostatic
Parking Brake	Independent
<b>DIFFERENTIAL LOCK</b>	
Differential Lock	Yes, Foot Operated
<b>PTO</b>	
PTO (rpm)	Mid PTO- 2100 RPM, Rear 540
PTO (actuation)	Electro hydraulic operated/mechanical selector lever
<b>STEERING</b>	
Steering	Power steering
<b>ELECTRICAL</b>	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
<b>HYDRAULICS</b>	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional hydraulic circuit	1 DA (ROPS) / 3DA (Cabin)

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

FEATURES		H26	
Hydraulic Lifting Capacity		775 Kg	
Lift Rods		Standard	
Litre Per Minute (LPM)		16.5	
SAFETY SWITCH 			
PTO Safety		Standard	
Neutral Safety Switch		Standard	
Clutch Safety Switch		Standard	
CAPACITY (LTRS)(+/-5%) 			
Fuel Tank (Lit)		22 (ROPS), 26 (CABIN)	
TURNING RADIUS 			
Without brakes (m) as per standard tyres		3.05 (RHS), 2.62 (LHS)	
TYRE 			
Front		6.00-12	
Rear		8.30-20	
DIMENSION & WEIGHT(+/-5%) 			
Weight (Kg)		1235	
Wheel Base (mm)		1570	
Total Length (mm)		2895	
Total Width (mm)		1290 (max)-1215 (min)	
Height (mm) Up to ROPS		2350	
Min Ground Clearance (mm)		215	
Front Track (mm)		885	
Rear Track (mm)		960	
OTHERS 			
Fuel Indicator Gauge		Standard	
Front Tow Hook		Standard	
Front & Rear Weights with std. Ballast		Front weights - 2 x 15 Kg	
Trailer Hitch		1. E-marked swinging drawbar 2. Clevis Hitch 3. Semi-Automatic hitch	
ROPS		Yes	
OPTIONAL FEATURES 			
Cabin Option		Yes	
TYRES			
			
Radial Agri: Front   Rear	Turf: Front   Rear	Ind: Front   Rear	Galaxy Pro: Front   Rear
6.5/80-12 280/70 R18	25x8,50-14 13.60-16	23x8,50-12 33x15,50-16,5	220/55R12 280/70R16
Additional Tyre		Front Tyre - 7*14   Rear Tyre - 8*24	
Front Loader		YES optional	

DEALER STAMP

## INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)  
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221  
Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com