

AMONG TOP **5 TRACTOR**MANUFACTURERS
GLOBALLY*



EMINENT PRESENCE IN 140+
COUNTRIES



JOINT VENTURE WITH **YANMAR** (JAPAN)



NO. 1 TRACTOR EXPORTER FROM



WORKFORCE OF **5,500+** DEDICATED EMPLOYEES WITH 400+ ENGINEERS IN R&D



PRODUCTION
CAPACITY OF **300,000**TRACTORS PER YEAR





Download! Solis Tractors APP

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com





SUSPENDED PLATFORM









3 CYLINDER STAGE V HIGH END TORQUE ENGINE











STAGE V SERIES

To meet the dynamic demands of farming, your farm tractor has to deliver maximum performance all day long.

Hardworking, versatile and easy to operate, Solis modern tractors are there for you to provide tremendous value for money over their working life. Not only do they deliver unmatched results and durability, but also result in a long-term investment that provides amazing results!

Experience the incredible innovation that leads you to perform beyond the boundaries. An innovation that will help you to transform your farm manoeuvres into exhilarating experiences.

Empowered with mighty features, farm excellence and a 3 cylinder stage V engine that emits low carbon emissions, resulting in a healthier ecosystem. The 12F + 12R synchromesh transmission enables smooth operability with 2500kg lifting capacity. Also, you get an S command centre and high backup torque of 215 Nm & 250 Nm to easily operate even on difficult terrains.

With this technology, Solis aims to deliver state-of-the-art quality to build a formidable future. To challenge the status quo and transform your aspirations into dreams. Solis is taking on an endeavour to bring a dawn of new hope.



NEW BENCHMARK OF

POWER

This mighty engine has incredible features to offer you, packed with unmatched technology that powers up efforts into breathtaking results! Embedded with state-of-the-art technology that transforms your farm experiences into remarkable results, the mighty Solis tractor engine has got what you are seeking! It comes with a dynamically balanced three-cylinder Stage V technology which consumes less fuel, thereby resulting in moulding a sustainable future. On top of that, it delivers high performance with the help of excellent power reserves.



STAGE V ENGINE

Green is the way, this series of tractors is equipped with the stage V engine. The globally acclaimed synchromesh speed helps every farmer to pace ahead towards international standards. Quiet yet powerful, the Stage V engine combines durability, productivity and ample power reserves to support your daily work. Moreover, Solis tractors deliver unmatched results and durability, resulting in long-term investment.


- Lower emissions
- Comes with high horse power 50 & 60 HP Category
- High end torque of 215 Nm & 250 Nm

- DOC + DPF ATS system
- TCIC fuel efficient engine
- Block heater (Opt.)



EASY MAINTENANCE

This engine encompasses varieties of features that result in setting new benchmarks of power. With high productivity and low maintenance, this engine proves to be the perfect fit for your farm. Moreover, it ensures low vibrations during all sorts of farm operations. Additionally, the ease of transmission and high range acceleration capacity enables the user to conquer any terrain easily. On top of that, the engine has been designed so that it can be easily serviced on your farm without any hustle which means, you can accelerate your productivity on your farm easily.





NEW BENCHMARK OF LIFTING

With the impeccable hydraulics of Solis tractors, witness the matchless potential of elevating ordinary to extraordinary. The hydraulic lifting capacity of the Solis tractor uplifts productivity and ensures less operational stress with an enhanced lifting capacity of 2500kg and a 45 LPM flow rate. This mighty tractor is empowered with a highly effective auto hitch facility and CAT-II three-point linkage that adds more precision to your success.

HYDRAULICS

S-8005T HYDRAULICS





NEW BENCHMARK
OF COMFORT

The stage V engine ensures to yield sustainable productivity. This tractor is dynamically built to let the user experience ease of working and comfort. Loaded with the 'S-Command Center' technology, this tractor offers a spacious operator seat, armrest and headrest so that you can work all day long tirelessly. Moreover, with an integrated joystick, you can behold the charm of smooth transmissions, that will not only help you work on the farm with ease but also reduce your load on the farm.





This series delivers a premium cab to create a comforting environment in the compartment. It is designed to provide you with extra space while operating. The cab has large glassy windows for an enormous view and clean visibility even when the driver's seat is in reverse position.

ALL-AROUND COMFORT

Our large cab is designed to ensure all-day comfort and less operational stress to the user. The pleasure of working in Solis tractor results in productive performance due to the absolute comfort. All the levers are ergonomically placed to enhance the user experience thereby making it great for long days at the wheel.

TILTABLE & TELESCOPIC STEERING

The steering wheel is completely designed that enables the user to pull the wheel closer or push it farther away. It lets you adjust according to your comfort with a TM perfect grip, resulting in smooth operability.

VERSATILE MACHINE EMPOWERING NATURE

Solis tractors combine practicality with versatility! These tractors adapt completely to your needs. With their powerful diesel engines, robust drive trains and large lifting capacity, Solis tractors are truly value for money. Not only these are all-rounders in the best sense but also impress with their valuable innovations!

CBM LADDER HITCH

Optional CBM Ladder Hitch offer simple, precise loading with its side-mounted controls. It also allows operators to do a plethora of works easily, such as lifting and loading seed or pre-germinated sorghum into rows. The primary benefit that the system provides is transferring the weight and resistance of an implement to the drive wheels of the tractor which gives the tractor more usable traction across the terrains.

AUTOMATIC HITCH/ SEMI AUTOMATIC HITCH

On top of that, other features such as Semi-Automatic and Automatic Hitch also provide promising results. The automatic hitch's ability to connect and disconnect reduces the need for the operator to get out of the cab.

QUICK ATTACH LOADER (OPT)

Versatile and precise the quick attach loader brings innovative design and user-friendly functions for the highest levels of efficiency. The feature offers simple, precise loading with its side-mounted controls that easily allow operators to lift and load seed or pre-germinated sorghum into rows.

MULTIPLE TYRE OPTIONS

Built to cater to all your needs, Solis tractors can work with different land types, terrains and topographies. This is because our tractors can work with a multitude of tyre options that can easily be utilised for all sorts of farm manoeuvres regardless of the field size and field type.



FEATURES	<i>\$5</i> 0	\$60	F
TL ENGINE 👸			
No. of cylinders / capacity (cc) / emissions level	3/ 3065/ CRDi Stage V	3/ 3065/ CRDi Stage V	
After treatment system	DOC + DPF	DOC + DPF	
Rated engine power (kw/Hp)	37.3/50	43.2/58	
Rated engine speed	2000	2000	
Max. torque (Nm)	215@1400 Rpm	250@1400 Rpm	
Aspiration	Turbo charged	Turbo charged	-
ntercooler	•	•	
Air Cleaner	Dual Stage Dry Type	Dual Stage Dry Type	
Block Heater	0	0	
Jpdraft Exhaust Pipe	•	•	
Oowndraft Exhaust Pipe	0	0	
Fuel tank capacity (L)	72	72	
TRANSMISSION #			
2x12 Synchro Shuttle transmission (4WD)	•	•	
Minimum forward speed	1.3kmph	1.3kmph	
Maximum forward speed	30kmph	30kmph	
2x12 Synchro Shuttle transmission (4WD) with Creeper	0	0	
Minimum forward speed	0.5kmph	0.5kmph	-
Maximum forward speed	30kmph	30kmph	
FRONT AXLE			
2WD Front Axle	0	0	
IWD Front Axle	•	•	
Differential Lock	Mechanical	Mechanical	
IWD Actuation	Mechanical	Mechanical	
Brake Actuation	Mechanical Assist	Mechanical Assist	
PTO			
РТО Туре	Mechanical	Mechanical	
540/540E	•	•	
540/1000	0	0	
540/ground speed	0	0	
HYDRAULIC O:			
lydraulic pump flow (lpm)	45	45	
Open center mechanical draft control	•	•	
op link draft sensing	•	•	
iftomatic system	0	0	
ift Capacity	2500 KG	2500 KG	
inkage Category	II	II	
Self Locking Linkages	0	0	
Max. no. of rear remotes	2/3 (Opt.)	2/3 (Opt.)	
Max. no. of Mid remotes	2	2	
Mechanical joystick control for mid nounts with valves	0	0	

Standard

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

E-Mark Swinging Drawbar	•	•
Cuna Type Ladder Hitch	0	0
Semi Automatic Ladder Hitch	0	0
Automatic Ladder Hitch	0	0
TRAILER BRAKES		
Without Trailer Brakes	•	•
Hydraulic Trailer Brakes	0	0
Dual Line Pneumatic Trailer Brakes	0	0
ELECTRICALS (ROPS/CAB)		
Battery	110AH 800CCA	110AH 800C0
Alternator	90A/120A	90A/120A
Button Operated Battery Cut off Switch, 3 Pinsocket, Seven On Trailer Socket	•	•
OPERATOR ENVIRONMENT		
Suspended platform (with ROPS)	•	•
Premium Driver seat	0	0
Tiltable & Telescopic Steering	0	0
Integrated Loader Joystick	0	0
Cabin Air Conditioning (With Cabin)	0	0
DIMENSIONS (ROPS/CAB)		
Wheelbase (mm)	2225	2225
Overall Height (mm)	2690/2480	2700/2500
Overall Width (mm)	1840-1880	1937
Overall Length (mm)	3825-4055	3841-4066
Front Track Width (mm)	1570	1570
Rear Track Width (mm)	1450	1475
Ground Clearance (mm)	310	335
Unladen Mass (Kg)	2870	2920
Tyre Combination	9.5x20 & 13.6x28	9.5x24 & 14.9
Optional Tyre Combinations		
Bias Tyres (2WD)	6x16 & 12.4x28	7.5x16 & 16.9
	6.0x16 & 13.6x28	-
	6.5x16 & 13.6x28	-
	7.5x16 & 14.9x28	-
Bias Tyres (4WD)	8.3x24 & 13.6x28	-
	9.5x20 & 14.9x28	9.5x24 & 16.9
Radial Tyres (4WD)	250/85R20 & 340/85R28	250/85 R24 & 420/8
	280/70R18 & 380/70R28	-
Industrial Tyres (4WD)	10-16.5 & 14.9-24	10-16.5 & 14.9
	12.5/80-18 & 18.4-24	12.5/80-18 & 18