





















ALL-ELECTRIC TRACTOR

INTRODUCING Solis SV26

TOUGHEST PERFORMER WITH ZERO EMISSIONS

FEATURES	SV26
MOTOR 	
Traction Motor	
Power	17 kw
Rated RPM	2500
BATTERY 	
Model	Li-Ion Battery
Rated Capacity	308Ah
Rated Voltage	76.8V
Auxillary Battery	20AH
TRANSMISSION 	
Drive	4WD
Clutch	Wet Type Clutch for PTO
Gearbox	Hydrostatic
Front Axle	4WD
Transmission	2-Stage Hydrostatic
SPEED (FORWARD) 	
Maximum Speed (Km/Hr)	19.67 @ full flyup 2700 RPM
Minimum Speed (Km/Hr)	2.91 @ 900 ERPM, 8.75 @ 2700 ERPM
BRAKES 	
Brakes	Oil Immersed Brakes
Type of Actuation	Single Push Pedal
Parking Brake	Independent
DIFFERENTIAL LOCK 	
Differential Lock	Yes, Foot Operated
PTO 	
PTO (rpm)	Mid PTO - 2100 RPM, Rear 540
PTO (actuation)	Electrohydraulic
STEERING 	
Steering	Power Steering
ELECTRICAL 	
Seven Pin Trailer Socket	Standard
HYDRAULICS 	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional Hydraulic Circuit	1 DA

FEATURES	SV26			
Hydraulic Lifting Capacity	Std. 600 & Opt. - 750			
Lift Rods	Standard			
Litre per Minute (LPM)	15.07 @ 2500 RPM			
SAFETY SWITCH 				
PTO Safety	Standard			
Neutral Safety Switch	Standard			
TURNING RADIUS 				
Without Brakes (m) as per Standard Tyres	3.4			
TYRE 				
Front	25*8.50-14			
Rear	13.6*16			
DIMENSION & WEIGHT(+/-5%) 				
Weight (Kg)	1365			
Wheel Base (mm)	1560			
Total Length (mm)	2960			
Total Width (mm)	1200			
Height (mm) Up to ROPS	2325			
Min Ground Clearance (mm)	210			
Front Track (mm)	940			
Rear Track (mm)	1000			
OTHERS 				
Front Tow Hook	Standard			
Trailer Hitch	E Mar Swinging Bar (Std), Clevis Hitch, Semi Automatic Hitch			
ROPS	Yes			
TYRES				
				
RADIAL AGRI Front 6.5/80-12 Rear 280/70 R18	AGRI Front 6x12 Rear 8.30x20	TURF Front 25x8,50-14 Rear 13.60-16	INDUSTRIAL Front 23x8,50-12 Rear 33x15,50-16,5	GALAXY PRO Front 220/55R12 Rear 280/70R16
Front loader		YES optional		

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All dimensions are with standard tyres.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 522220, 522221
Fax: +91 1882 522222 | Email: info@solisworld.com | URL: www.solistractors.com





Zero Emissions



Optional Fast Charging -
Outboard AC charger
(3.5hrs, 0-80%)



Constant Torque
and Power



On-board AC Charging



Minimal Noise
& Vibrations



S-Comfort Package with
better ergonomics
(Driver seat - armrest & head
rest, Wide Workspace)



Lesser Operational
Cost Zero
Maintenance Cost



2 - Range HST
Transmission



76.8V 308Ah Li-ion Battery
Bigger Battery for
Long Running



15.07 LPM Hydraulic
Pump Flow (Best in
segment)




Battery Life of
10 Years or 3000 cycles
(@80% DOD)



Electro Hydraulic
Independent PTO @
Rear & @Mid



Heating Battery Package
for Lower Temperature
Conditions



Multiple Tyre Options
(Agricultural Bias & Radial,
Industrial, Turf & Galaxy Pro)